



Specifications vary by plant

## **Standard Features**

- Tube Main Frame Construction
- 24" O.C. Frame
- 16" O.C. Sidewalls
- 16" O.C. Roof Bows
- Spring Axles w/EZ-Lube Hubs
- Electric Brakes w/ Breakaway & Battery Box
- 15" Radial Tires
- 2" Coupler
- Safety Chains
- Single Tube Tongue
- 3/4" High Performance Floor
- High Performance Wall Liner
- Aluminum Exterior
- 1 Piece Aluminum Roof
- 24" Stoneguard
- Rear Ramp Door w/ Spring Assist
- Double Front Ramp Doors with Spring Assist
- 7-Way Plug
- LED Tail and Clearance Lights
- (1) Dome Light
- Transport Canada Certified Tie Downs
- Moisture Barrier (IN / UT / PA)
- Automotive Undercoating
- Limited 3 Year Warranty





Optional Equipment May Be Shown

	WHITEOUT 8.5' WIDE SNOWMOBILE / ATV TRAILER
	PWFT 85X12 SE2
Overall Length	19'10"
Width	101"
Height	96"
Interior Length	14'2"
Interior Width	96"
Interior Height	67.5"
Platform Height	25"
Rear Opening Height	62"
Rear Opening Width	93.5"
Front Ramp Open Height	62"
Front Ramp Open Width	50"
Hitch Ball Height	22"
Hitch Ball Size	2"
Brakes	ELECTRIC
GVWR	3500#
Hitch Weight	350#
Curb Weight	2300#
Payload Capacity	1200#
Tires	ST205/75R15
Wheels	E-COAT
Frame	TUBE
Sidewalls	High Performance Wall Liner
Floor	3/4"
Ceiling	ОРТ
Tail Lights	LED
Clearance Lights	LED
Dome Light	1
Sidewall Vents	ОРТ
Stone Guard	24"
V-Nose	STD
Side Door	ОРТ
Tie Downs	4
Sand Pad	STD
Side Posts	16" O.C.
Roof Bows	16" O.C.
Crossmembers	24" O.C.
Axle	SPRING
EZ Lube	YES
Undercoat	Automotive