

### STANDARD FEATURES

Flat Top Round Front  
6" Tube Main Frame  
16" On-Center Full Height Crossmembers  
6" A-Frame Triple Tube Tongue  
16" On-Center Tube Sidewalls  
78" Interior Height  
16" On-Center Roof Bows  
2-5/16" A-Frame Ball Coupler  
Safety Chains  
2K Coupler Mounted Jack  
Torsion Brake Axle(s)  
Superlube Hubs

15" Silver Steel Wheels  
High Performance Wood Walls and Trim  
3/4" High Performance Wood Flooring  
Automotive Undercoating  
Lauan Ceiling Liner Strip  
(4) 5K Zinc D-Rings  
7-Way Electric Plug  
Breakaway Battery with Switch  
Bullet LED Marker and Clearance Lights  
Slimline LED Tail Lights with Integrated Backup Light  
(2) LED Dome Light(s) with Switch  
0.030 Aluminum Exterior

Color Matching Rear Hoop  
White, Black, Silver, Pewter, Charcoal  
Screwless Exterior  
24" Tall Straight ATP Stone Guard  
2.5" Top Trim  
3" Bottom Trim  
TPO Cap  
Seamless Aluminum Roof  
36" Wide Entry Door with Flush Lock  
Cast Aluminum Door Holdback  
Rear Ramp Door with Spring Assist  
Sidewall Vents

### 7 WIDE MODELS

MODEL	7 x 12	7 x 14	7 x 16	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	7 x 18	7 x 20
MODEL #	KP8412TBFB-070	KP8414TBFB-070	KP8416TBFB-070	KP8412TBFB-100	KP8414TBFB-100	KP8416TBFB-100	KP8418TBFB-070	KP8420TBFB-070	KP8418TBFB-100	KP8420TBFB-100
GVWR	7000			9900			7000		9900	
TIRES	ST205/75R15 'C' Radial Tires			ST225/75R15 'D' Radial Tires			ST205/75R15 'C' Radial Tires		ST225/75R15 'D' Radial Tires	

Smooth Aluminum Fenders

RAMP DOOR CAPACITY : 2500

### 8.5 WIDE MODELS

MODEL	8.5 x 12	8.5 x 14	8.5 x 16	8.5 x 12	8.5 x 14	8.5 x 16
MODEL #	KP10212TBFB-070	KP10214TBFB-070	KP10216TBFB-070	KP10212TBFB-100	KP10214TBFB-100	KP10216TBFB-100
GVWR	7000			9900		
TIRES	ST205/75R15 'C' Radial Tires			ST225/75R15 'D' Radial Tires		

MODEL	8.5 x 18	8.5 x 20	8.5 x 18	8.5 x 20
MODEL #	KP10218TBFB-070	KP10220TBFB-070	KP10218TBFB-100	KP10220TBFB-100
GVWR	7000		9900	
TIRES	ST205/75R15 'C' Radial Tires		ST225/75R15 'D' Radial Tires	

Smooth Aluminum Fender Flares  
Interior Recessed Step  
RAMP DOOR CAPACITY : 4000

