



	8.5 x 17	8.5 x 19	8.5 x 21	8.5 x 23	8.5 x 25	8.5 x 27
Model #	KP10217ELFVMS-100	KP10219ELFVMS-100	KP10221ELFVMS-100	KP10223ELFVMS-100	KP10225ELFVMS-100	KP10227ELFVMS-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Tube with Center Drawbar, Max Extension					
Crossmembers	Steel Formed Channel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Straight, Equalizer Brackets					
Safety Chains	DOT Compliant					
Tongue Jack	5K Drop Leg, Frame Mounted					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	60" Aero Wedge					
Beavertail	24"	32"	48"			
Ramp(s)	12" Extension (Both Ramps), 4000 lb. with Assist, 61" Front Wedge with Assist					
Side Door	24" Wide Flush Lock, Wire Holdback	32" Wide Flush Lock, Wire Holdback	36" Wide Flush Lock, Wire Holdback			
Vents	Sidewall Airflow					
Fenders	Smooth Aluminum					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Steel					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	1.5" Bottom Extrusion, 2.5" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop					
Stone Guard	24" ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Lauan Strip					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





JOURNEY MOTORSPORT
JOURNEY FLAT TOP V-NOSE 10K

	8.5 x 17	8.5 x 19	8.5 x 21	8.5 x 23	8.5 x 25	8.5 x 27
Switches	(1) Dome Light, 12V					
Cargo Control	(4) 5000 lb. Recessed D-Rings, (9) 2.5K Recessed D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 29	8.5 x 31	8.5 x 33	8.5 x 35	8.5 x 37
Model #	KP10229ELFVMS-100	KP10231ELFVMS-100	KP10233ELFVMS-100	KP10235ELFVMS-100	KP10237ELFVMS-100
CAPACITIES					
GVWR (lbs)	9900				
GAWR (lbs/axle)	5000				
CHASSIS					
Frame	6" x 2" Steel Tube		8" x 2" Steel Tube		
Tongue	6" x 2" Steel Tube with Center Drawbar, Max Extension		8" x 2" Steel Tube with Center Drawbar, Max Extension		
Crossmembers	Steel Formed Channel, 16" On-Center				
Integrated Step(s)	Interior Recessed				
Coupler	2-5/16" Straight, Equalizer Brackets				
Safety Chains	DOT Compliant				
Tongue Jack	5K Drop Leg, Frame Mounted				
Wall Studs	Steel Tube, 16" On-Center				
Roof Bows	Steel Tube, 16" On-Center				
Front Profile	60" Aero Wedge				
Beavertail	48"				
Ramp(s)	12" Extension (Both Ramps), 4000 lb. with Assist, 61" Front Wedge with Assist				
Side Door	36" Wide Flush Lock, Wire Holdback				
Vents	Sidewall Airflow				
Fenders	Smooth Aluminum				
Axle	(2) 5200 lb. Drop Spring Brake				
Hubs	Easy Lube				
Breakaway	Battery, Switch, and Lanyard				
Tires	ST225/75R15D 8-PR				
Wheels	15", 6-Hole Steel				
Exterior Finish	.030" Aluminum				
Undercoating	Automotive				
Exterior Fastening	VHB Bonded (Screwless)				
Exterior Trim	1.5" Bottom Extrusion, 2.5" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop				
Stone Guard	24" ATP				
Roof	Flat Top Seamless Aluminum				
Interior Walls	Engineered Wood				
Interior Trim	Extruded Aluminum Wall Transitions				
Ceiling	Luan Strip				
Flooring	3/4" Engineered Wood				
Interior Lights	(2) LED				
Switches	(1) Dome Light, 12V				
Cargo Control	(4) 5000 lb. Recessed D-Rings, (9) 2.5K Recessed D-Rings				

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



JOURNEY MOTORSPORT
JOURNEY FLAT TOP V-NOSE 10K

	8.5 x 29	8.5 x 31	8.5 x 33	8.5 x 35	8.5 x 37
Connector Plug	Round 7-pin Blade				
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights				



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

	8.5 x 17	8.5 x 19	8.5 x 21	8.5 x 23
Model #	KP10217ELFVMS-070	KP10219ELFVMS-070	KP10221ELFVMS-070	KP10223ELFVMS-070
CAPACITIES				
GVWR (lbs)	7000			
GAWR (lbs/axle)	3500			
CHASSIS				
Frame	6" x 2" Steel Tube			
Tongue	6" x 2" Steel Tube with Center Drawbar, Max Extension			
Crossmembers	Steel Formed Channel, 16" On-Center			
Integrated Step(s)	Interior Recessed			
Coupler	2-5/16" Straight, Equalizer Brackets			
Safety Chains	DOT Compliant			
Tongue Jack	5K Drop Leg, Frame Mounted			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	60" Aero Wedge			
Beavertail	24"	32"	48"	
Ramp(s)	12" Extension (Both Ramps), 4000 lb. with Assist, 61" Front Wedge with Assist			
Side Door	24" Wide Flush Lock, Wire Holdback	32" Wide Flush Lock, Wire Holdback	36" Wide Flush Lock, Wire Holdback	
Vents	Sidewall Airflow			
Fenders	Smooth Aluminum			
Axle	(2) 3500 lb. Drop Spring Brake			
Hubs	Easy Lube			
Breakaway	Battery, Switch, and Lanyard			
Tires	ST205/75R15C 6-PR			
Wheels	15", 5-Hole Steel			
Exterior Finish	.030" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	1.5" Bottom Extrusion, 2.5" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop			
Stone Guard	24" ATP			
Roof	Flat Top Seamless Aluminum			
Interior Walls	Engineered Wood			
Interior Trim	Engineered Wood Wall Transitions			
Ceiling	Lauan Strip			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) LED			
Cargo Control	(4) 5000 lb. Recessed D-Rings, (9) 2.5K Recessed D-Rings			
Connector Plug	Round 7-pin Blade			
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.