SHADOW GT GOOSENECK RACE SHADOW GT FLAT TOP FLAT FRONT 14K



	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34					
Model #	KP10228PRFBGNRT-140	KP10230PRFBGNRT-140	KP10232PRFBGNRT-140	KP10234PRFBGNRT-140					
CAPACITIES									
GVWR (lbs)	14000								
GAWR (lbs/axle)		70	00						
CHASSIS									
Frame		0" v 0" C	teel Tube						
Tongue			eneck						
Crossmembers			16" On-Center						
Coupler		-	ooseneck						
Safety Chains		-,	mpliant						
Tongue Jack			ed Landing Gear						
Wall Studs		•	6" On-Center						
Roof Bows		•	6" On-Center						
Front Profile		·	at						
Beavertail			8"						
Ramp(s)	16" Exte	40 16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist							
Side Door		uminum Pull-Out Step, 48" Wide							
Access Doors		•	" in Riser						
Vents		(1) Manual Roof,	Sidewall Airflow						
Fenders		Extruded	Aluminum						
Axle		(2) 7000 lb. Torsion Brake,	Spread Axle Configuration						
Hubs		Easy	Lube						
Breakaway		Battery, Switc	h, and Lanyard						
Tires		ST235/80F	R16E 10-PR						
Wheels		16", 8-Hole	Aluminum						
Exterior Finish		.040" Al	uminum						
Undercoating		Autor	notive						
Exterior Fastening		VHB Bonded	(Screwless)						
Exterior Trim	5.5" Bottom Extrusion, ATF	Riser Wall, Heavy Duty Truck E Stainless Steel Radius Corne	ody Top Extrusion, Polished Ca rs, Stainless Steel Rear Hoop	st Aluminum Roof Corners,					
Rear Spoiler		6" Stainless Stee	l Flare with Taper						
Roof		Flat Top Seam	less Aluminum						
Roof Cap		Stainle	ss Steel						
Interior Walls		Aluminum Overlay	, Engineered Wood						
Interior Trim		Extruded Aluminu	m Wall Transitions						
Ceiling	Insulat	tion, Vinyl Ceiling Transitions, V	/hite Vinyl Liner with Aluminum	Coves					
Flooring		3/4" Engine	eered Wood						
Interior Lights		. ,	" LED						
Switches		(1) Top Fuel Dome Light, 12V	, (1) Top Fuel Load Light, 12V						





SHADOW GT FLAT TOP FLAT FRONT 14K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34		
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
HVAC	Bracing and Wire for HVAC					



SHADOW GT GOOSENECK RACE SHADOW GT FLAT TOP FLAT FRONT 10K



	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34					
Model #	KP10228PRFBGNRT-100	KP10230PRFBGNRT-100	KP10232PRFBGNRT-100	KP10234PRFBGNRT-100					
CAPACITIES									
GVWR (lbs)	9900								
GAWR (lbs/axle)	5000								
CHASSIS									
Frame -		8" x 2" Si							
Tongue			eneck						
Crossmembers		•	16" On-Center						
Coupler			ooseneck						
Safety Chains			mpliant						
Tongue Jack		Dual 12K, 2-Spe	•						
Wall Studs			6" On-Center						
Roof Bows		•	6" On-Center						
Front Profile			at						
Beavertail		4							
Ramp(s)		nsion with Bullnose Cap, (2) Re							
Side Door	48" Alt	Iminum Pull-Out Step, 48" Wide		ldback					
Access Doors			' in Riser						
Vents		(1) Manual Roof,							
Fenders		Extruded							
Axle			Spread Axle Configuration						
Hubs		•	Lube						
Breakaway			h, and Lanyard						
Tires		, .	R15D 8-PR						
Wheels		15", 6-Hole							
Exterior Finish			uminum						
Undercoating			notive						
Exterior Fastening		VHB Bonded	• •						
Exterior Trim	5.5" Bottom Extrusion, ATF	Riser Wall, Heavy Duty Truck B Stainless Steel Radius Corne	ody Top Extrusion, Polished Ca rs, Stainless Steel Rear Hoop	st Aluminum Roof Corners,					
Rear Spoiler		6" Stainless Stee	l Flare with Taper						
Roof		Flat Top Seam	less Aluminum						
Roof Cap		Stainles	ss Steel						
Interior Walls		Aluminum Overlay	, Engineered Wood						
Interior Trim		Extruded Aluminu	m Wall Transitions						
Ceiling	Insulat	ion, Vinyl Ceiling Transitions, V	/hite Vinyl Liner with Aluminum	Coves					
Flooring		3/4" Engine	eered Wood						
Interior Lights		(2) 11	" LED						
Switches		(1) Top Fuel Dome Light, 12V	, (1) Top Fuel Load Light, 12V						





SHADOW GT FLAT TOP FLAT FRONT 10K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34		
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug		Round 7-	pin Blade			
Exterior Lights	(2) Rear LED Loading,	(4) Additional Stop/Turn/Tail, I	Full LED, DOT Compliant, Integra	ated Backup/Taillights		
HVAC	Bracing and Wire for HVAC					



SHADOW GT GOOSENECK RACE SHADOW GT FLAT TOP FLAT FRONT 15K



	8.5 x 30	8.5 x 32	8.5 x 34	8.5 x 36	8.5 x 38					
Model #	KP10230PRFBGNRT-	KP10232PRFBGNRT-	KP10234PRFBGNRT-	KP10236PRFBGNRT-	KP10238PRFBGNRT-					
Model #	150	150	150	150	150					
CAPACITIES										
GVWR (lbs)			15000							
GAWR (lbs/axle)		5000								
CHASSIS										
Frame			8" x 2" Steel Tube							
Tongue			Gooseneck							
Crossmembers		F	ormed Steel, 16" On-Cent	er						
Coupler			2-5/16" Gooseneck							
Safety Chains			DOT Compliant							
Tongue Jack		Dual 12K, 2-Speed Landing Gear								
Wall Studs		Steel Tube, 16" On-Center								
Roof Bows		Steel Tube, 16" On-Center								
Front Profile		Flat								
Beavertail			48"							
Ramp(s)	16	5" Extension with Bullnos	e Cap, (2) Recessed Cam	Locks, 4000 lb. with Ass	ist					
Side Door		48" Aluminum Pull-Out S	tep, 48" Wide Flush Lock,	Cast Aluminum Holdbac	k					
Access Doors			16" x 48" in Riser							
Vents		(1)	Manual Roof, Sidewall Aiı	flow						
Fenders			Extruded Aluminum							
Axle		(3) 5200 lb. T	orsion Brake, Spread Axle	Configuration						
Hubs			Easy Lube							
Breakaway		В	attery, Switch, and Lanya	rd						
Tires			ST225/75R15D 8-PR							
Wheels			15", 6-Hole Aluminum							
Exterior Finish			.040" Aluminum							
Undercoating			Automotive							
Exterior Fastening			VHB Bonded (Screwless)							
Exterior Trim	5.5" Bottom Extrusio	•	Duty Truck Body Top Ext Radius Corners, Stainless	•	minum Roof Corners,					
Rear Spoiler			tainless Steel Flare with 1							
Roof			lat Top Seamless Aluminu	•						
Roof Cap			Stainless Steel							
Interior Walls		Alum	inum Overlay, Engineered	Wood						
Interior Trim			ded Aluminum Wall Trans							
Ceiling		Insulation, Vinyl Ceiling	Fransitions, White Vinyl Li	ner with Aluminum Cove	S					
Flooring			3/4" Engineered Wood							
Interior Lights			(2) 11" LED							





SHADOW GT FLAT TOP FLAT FRONT 15K

	8.5 x 30	8.5 x 32	8.5 x 34	8.5 x 36	8.5 x 38		
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V						
Cargo Control		(4) 5000 lb. Recessed D-Ri	ngs			
Connector Plug			Round 7-pin Blade				
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights						
HVAC	Bracing and Wire for HVAC						



SHADOW GT GOOSENECK RACE SHADOW GT FLAT TOP FLAT FRONT 16K



	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34					
Model #	KP10228PRFBGNRT-160	KP10230PRFBGNRT-160	KP10232PRFBGNRT-160	KP10234PRFBGNRT-160					
CAPACITIES									
GVWR (lbs)	16000								
GAWR (lbs/axle)	8000								
CHASSIS									
Frame -		8" x 2" Si							
Tongue		Goos							
Crossmembers		-	16" On-Center						
Coupler		2-5/16" G							
Safety Chains			mpliant						
Tongue Jack		Dual 12K, 2-Spe	-						
Wall Studs		-	6" On-Center						
Roof Bows		•	6" On-Center						
Front Profile		FI							
Beavertail		4		··· • ·					
Ramp(s)		nsion with Bullnose Cap, (2) Re							
Side Door	48" Alt	Iminum Pull-Out Step, 48" Wide		Idback					
Access Doors			' in Riser						
Vents		(1) Manual Roof,							
Fenders		Extruded /							
Axle			Spread Axle Configuration						
Hubs		Oil I							
Breakaway		Battery, Switch	•						
Tires		215/75R17							
Wheels		17.5", 8-Hol	e Aluminum uminum						
Exterior Finish									
Undercoating			notive						
Exterior Fastening		VHB Bonded	• •						
Exterior Trim	5.5 Bottom Extrusion, ATF	Riser Wall, Heavy Duty Truck B Stainless Steel Radius Corne		st Aluminum Roof Corners,					
Rear Spoiler		6" Stainless Stee	l Flare with Taper						
Roof		Flat Top Seam	less Aluminum						
Roof Cap		Stainles	ss Steel						
Interior Walls		Aluminum Overlay	, Engineered Wood						
Interior Trim		Extruded Aluminu	m Wall Transitions						
Ceiling	Insulat	ion, Vinyl Ceiling Transitions, W	/hite Vinyl Liner with Aluminum	Coves					
Flooring		3/4" Engine	ered Wood						
Interior Lights		(2) 11	" LED						
Switches		(1) Top Fuel Dome Light, 12V	, (1) Top Fuel Load Light, 12V						





SHADOW GT FLAT TOP FLAT FRONT 16K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34		
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
HVAC	Bracing and Wire for HVAC					



SHADOW GT GOOSENECK RACE SHADOW GT FLAT TOP FLAT FRONT 21K



	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50			
Model #	KP10240PRFBGNRT-	KP10242PRFBGNRT-	KP10244PRFBGNRT-	KP10246PRFBGNRT-	KP10248PRFBGNRT-	KP10250PRFBGNRT-			
Mouel #	210	210	210	210	210	210			
CAPACITIES									
GVWR (lbs)			21	000					
GAWR (lbs/axle)			70	00					
CHASSIS									
Frame			8" v 2" S	teel Tube					
Tongue				eneck					
Crossmembers				16" On-Center					
Coupler				ooseneck					
Safety Chains			-	mpliant					
Tongue Jack				ed Landing Gear					
Wall Studs			· · ·	6" On-Center					
Roof Bows			•	6" On-Center					
Front Profile			-	at					
Beavertail				8"					
Ramp(s)		16" Extension wit	th Bullnose Cap, (2) Re	cessed Cam Locks, 40	00 lb. with Assist				
Side Door			Pull-Out Step, 48" Wide						
Access Doors			16" x 48	" in Riser					
Vents			(1) Manual Roof	, Sidewall Airflow					
Fenders			Extruded	Aluminum					
Axle		(3)	7000 lb. Torsion Brake,	Spread Axle Configura	ation				
Hubs			Easy	Lube					
Breakaway			Battery, Switc	h, and Lanyard					
Tires			ST235/80	R16E 10-PR					
Wheels			16", 8-Hole	e Aluminum					
Exterior Finish			.040" A	uminum					
Undercoating			Autor	notive					
Exterior Fastening				l (Screwless)					
Exterior Trim	5.5" Bottom Extrusio	n, ATP Riser Wall, Hea	vy Duty Truck Body Top	•	ast Aluminum Roof Co	rners, Stainless Steel			
				less Steel Rear Hoop					
Rear Spoiler				l Flare with Taper					
Roof			•	less Aluminum					
Roof Cap				ss Steel					
Interior Walls			•	, Engineered Wood					
Interior Trim		Inculation View		m Wall Transitions	luminum Course				
Ceiling		insulation, viny	/I Ceiling Transitions, V		aummum Coves				
Flooring Interior Lights				eered Wood I" LED					
Interior Lights Switches		(1) To	p Fuel Dome Light, 12V		ht 12V				
Switches Cargo Control		(1) 10		, (T) TOP Fuel Load Lig cessed D-Rings	III, I∠V				
Cargo Control Connector Plug			• •	pin Blade					
Connector Plug			Kound /-	ріп віаце					





SHADOW GT FLAT TOP FLAT FRONT 21K

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50	
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights						
HVAC	Bracing and Wire for HVAC						





HVAC	Bracing and Wire for HVAC
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights
Connector Plug	Round 7-pin Blade
Cargo Control	(4) 5000 lb. Recessed D-Rings
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
Interior Lights	(2) 11" LED
Flooring	3/4" Engineered Wood
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves
Interior Trim	Extruded Aluminum Wall Transitions
Interior Walls	Aluminum Overlay, Engineered Wood
Roof Cap	Stainless Steel
Roof	Flat Top Seamless Aluminum
Rear Spoiler	6" Stainless Steel Flare with Taper
	Radius Corners, Stainless Steel Rear Hoop
Exterior Trim	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel
Exterior Fastening	VHB Bonded (Screwless)
Undercoating	Automotive
Exterior Finish	.040" Aluminum
Wheels	16", 8-Hole Aluminum
Tires	ST235/80R16E 10-PR
Breakaway	Battery, Switch, and Lanyard
Hubs	Easy Lube
Axle	(3) 7000 lb. Torsion Brake, Spread Axle Configuration
Fenders	Extruded Aluminum
Vents	(1) Manual Roof, Sidewall Airflow
Access Doors	16" x 48" in Riser
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist
Beavertail	48"
Front Profile	Flat
Roof Bows	Steel Tube, 16" On-Center
Wall Studs	Steel Tube, 16" On-Center
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Safety Chains	DOT Compliant
Coupler	2-5/16" Gooseneck
Crossmembers	Formed Steel, 16" On-Center
Tongue	Gooseneck
Frame	8" x 2" Steel Tube
CHASSIS	
	/000
GVWR (lbs) GAWR (lbs/axle)	7000
	21000
CAPACITIES	
Model #	KP10252PRFBGNRT-210
	8.5 x 52



SHADOW GT GOOSENECK RACE SHADOW GT FLAT TOP FLAT FRONT 24K



	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50				
Model #	KP10240PRFBGNRT-	KP10242PRFBGNRT-	KP10244PRFBGNRT-	KP10246PRFBGNRT-	KP10248PRFBGNRT-	KP10250PRFBGNRT-				
Mouel #	240	240	240	240	240	240				
CAPACITIES										
GVWR (lbs)		24000								
GAWR (lbs/axle)			80	00						
CHASSIS										
Frame			8" x 2" S	teel Tube						
Tongue			Goos	eneck						
Crossmembers			Formed Steel,	16" On-Center						
Coupler			2-5/16" G	ooseneck						
Safety Chains			DOT Co	mpliant						
Tongue Jack			Dual 12K, 2-Spe	ed Landing Gear						
Wall Studs			Steel Tube, 1	6" On-Center						
Roof Bows			Steel Tube, 1	6" On-Center						
Front Profile			FI	at						
Beavertail			4	8"						
Ramp(s)		16" Extension wit	th Bullnose Cap, (2) Re	cessed Cam Locks, 40	00 lb. with Assist					
Side Door		48" Aluminum I	Pull-Out Step, 48" Wide	Flush Lock, Cast Alun	ninum Holdback					
Access Doors			16" x 48	" in Riser						
Vents			(1) Manual Roof,	Sidewall Airflow						
Fenders			Extruded	Aluminum						
Axle		(3)	8000 lb. Torsion Brake,	Spread Axle Configura	ation					
Hubs			Oil	Bath						
Breakaway			Battery, Switc	h, and Lanyard						
Tires			215/75R1	7.5J 18-PR						
Wheels				e Aluminum						
Exterior Finish			.040" Al	uminum						
Undercoating				notive						
Exterior Fastening				(Screwless)						
Exterior Trim	5.5" Bottom Extrusio	n, ATP Riser Wall, Hea	vy Duty Truck Body Top		ast Aluminum Roof Co	rners, Stainless Steel				
				less Steel Rear Hoop						
Rear Spoiler				I Flare with Taper						
Roof Roof Con			•	less Aluminum ss Steel						
Roof Cap Interior Walls										
Interior Wans			•	, Engineered Wood m Wall Transitions						
		Inculation Vin			luminum Couco					
Ceiling Flooring		insulation, viny	/I Ceiling Transitions, V	eered Wood	aummum Coves					
Interior Lights				" LED						
Switches		(1) To	ر (2) ا p Fuel Dome Light, 12V		ht 12V					
Cargo Control		(1) 10		, (T) TOP Fuel Load Lig cessed D-Rings	III, I∠V					
Connector Plug			• •	pin Blade						
connector Plug			Kouna /-							





SHADOW GT FLAT TOP FLAT FRONT 24K

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
HVAC	Bracing and Wire for HVAC					





SHADOW GT GOOSENECK RACE SHADOW GT FLAT TOP FLAT FRONT 24K

	8.5 x 52				
Model #	KP10252PRFBGNRT-240				
CAPACITIES					
	24000				
GVWR (lbs)	24000 8000				
GAWR (lbs/axle)	8000				
CHASSIS					
Frame	8" x 2" Steel Tube				
Tongue	Gooseneck				
Crossmembers	Formed Steel, 16" On-Center				
Coupler	2-5/16" Gooseneck				
Safety Chains	DOT Compliant				
Tongue Jack	Dual 12K, 2-Speed Landing Gear				
Wall Studs	Steel Tube, 16" On-Center				
Roof Bows	Steel Tube, 16" On-Center				
Front Profile	Flat				
Beavertail	48"				
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist				
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback				
Access Doors	16" x 48" in Riser				
Vents	(1) Manual Roof, Sidewall Airflow				
Fenders	Extruded Aluminum				
Axle	(3) 8000 lb. Torsion Brake, Spread Axle Configuration				
Hubs	Oil Bath				
Breakaway	Battery, Switch, and Lanyard				
Tires	215/75R17.5J 18-PR				
Wheels	17.5", 8-Hole Aluminum				
Exterior Finish	.040" Aluminum				
Undercoating	Automotive				
Exterior Fastening	VHB Bonded (Screwless)				
Exterior Trim	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel				
	Radius Corners, Stainless Steel Rear Hoop				
Rear Spoiler	6" Stainless Steel Flare with Taper				
Roof	Flat Top Seamless Aluminum				
Roof Cap	Stainless Steel				
Interior Walls	Aluminum Overlay, Engineered Wood				
Interior Trim	Extruded Aluminum Wall Transitions				
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves				
Flooring	3/4" Engineered Wood				
Interior Lights	(2) 11" LED				
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V				
Cargo Control	(4) 5000 lb. Recessed D-Rings				
Connector Plug	Round 7-pin Blade				
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights				
HVAC	Bracing and Wire for HVAC				

