

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30			
	KP10220PRFBRT-	KP10222PRFBRT-	KP10224PRFBRT-	KP10226PRFBRT-	KP10228PRFBRT-	KP10230PRFBRT-			
Model #	100	100	100	100	100	100			
CAPACITIES									
GVWR (lbs)			99	00					
GAWR (lbs/axle)			50	00					
CHASSIS									
Frame		6" x 2" Steel Tube 8" x 2" Steel Tube							
Tongue		12" Extension, 6" x	2" Steel Triple Tube		12" Extension, 8" x	2" Steel Triple Tube			
Crossmembers			Formed Steel,	16" On-Center					
Coupler			2-5/16" <i>A</i>	djustable					
Safety Chains			DOT Co	mpliant					
Tongue Jack			7K Drop Le	g, Set-Back					
Wall Studs			Steel Tube, 1	6" On-Center					
Roof Bows			Steel Tube, 1	6" On-Center					
Front Profile			F	at					
Beavertail	32"			48"					
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist								
Side Door		48" Aluminum Pเ	ıll-Out Step, 48" Wide	Flush Lock, Cast Alu	ıminum Holdback				
Vents	(1) Manual Roof, Sidewall Airflow								
Fenders			Extruded	Aluminum					
Axle		(2) 52	200 lb. Torsion Brake,	Spread Axle Configu	ıration				
Hubs			Easy	Lube					
Breakaway			Battery, Switc	h, and Lanyard					
Tires			ST225/75	R15D 8-PR					
Wheels			•	e Aluminum					
Exterior Finish			.040" A	uminum					
Undercoating				notive					
Exterior Fastening				l (Screwless)					
Exterior Trim	5.5" Bottom Ext	rusion, Heavy Duty Tr	• •			s, Stainless Steel			
			Radius Corners, Stair		0				
Stone Guard				ATP					
Rear Spoiler				l Flare with Taper					
Roof			•	less Aluminum					
Roof Cap				ss Steel					
Interior Walls			•	, Engineered Wood					
Interior Trim				m Wall Transitions					
Ceiling		Insulation, Vinyl	Ceiling Transitions, V	•	Aluminum Coves				
Flooring				eered Wood					
Interior Lights			(2) 1	I" LED					







	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30			
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V								
Cargo Control	(4) 5000 lb. Recessed D-Rings								
Connector Plug	Round 7-pin Blade								
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights								
HVAC	Bracing and Wire for HVAC								





	8.5 x 32
Model #	KP10232PRFBRT-100
CAPACITIES	
	2022
GVWR (lbs)	9900
GAWR (lbs/axle)	5000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	12" Extension, 8" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center
Coupler	2-5/16" Adjustable
Safety Chains	DOT Compliant
Tongue Jack	7K Drop Leg, Set-Back
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	Flat
Beavertail	48"
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback
Vents	(1) Manual Roof, Sidewall Airflow
Fenders	Extruded Aluminum
Axle	(2) 5200 lb. Torsion Brake, Spread Axle Configuration
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST225/75R15D 8-PR
Wheels	15", 6-Hole Aluminum
Exterior Finish	.040" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel
	Radius Corners, Stainless Steel Rear Hoop
Stone Guard	24" ATP
Rear Spoiler	6" Stainless Steel Flare with Taper
Roof	Flat Top Seamless Aluminum
Roof Cap	Stainless Steel
Interior Walls	Aluminum Overlay, Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves
Flooring	3/4" Engineered Wood
Interior Lights	(2) 11" LED
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings







	8.5 x 32
Connector Plug	Round 7-pin Blade
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights
HVAC	Bracing and Wire for HVAC





	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30				
No dol #	KP10220PRFBRT-	KP10222PRFBRT-	KP10224PRFBRT-	KP10226PRFBRT-	KP10228PRFBRT-	KP10230PRFBRT-				
Model #	140	140	140	140	140	140				
CAPACITIES										
GVWR (lbs)		14000								
GAWR (lbs/axle)		6000 7000								
CHASSIS										
Frame		8" x 2" Steel Tube								
Tongue			12" Extension, 8" x	2" Steel Triple Tube						
Crossmembers			Formed Steel,	16" On-Center						
Coupler			2-5/16" <i>A</i>	djustable						
Safety Chains			DOT Co	mpliant						
Tongue Jack			7K Drop Le	g, Set-Back						
Wall Studs			Steel Tube, 1	6" On-Center						
Roof Bows			Steel Tube, 1	6" On-Center						
Front Profile			Fl	at						
Beavertail	32"			48"						
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist									
Side Door		48" Aluminum Pu	•	Flush Lock, Cast Alu	ıminum Holdback					
Vents	(1) Manual Roof, Sidewall Airflow									
Fenders				Aluminum						
Axle		(2) 70		Spread Axle Configu	ration					
Hubs				Lube						
Breakaway			• "	h, and Lanyard						
Tires				R16E 10-PR						
Wheels			•	e Aluminum						
Exterior Finish				uminum						
Undercoating				notive						
Exterior Fastening	E E" Pottom Ext	rusion Hoovy Duty Tr		l (Screwless)	uminum Doof Corner	Ctainless Ctasl				
Exterior Trim	5.5 BULLOIN EXT		• •	on, Polished Cast Alı ıless Steel Rear Hoop		s, stailless steel				
Stone Guard				ATP	,					
Rear Spoiler				l Flare with Taper						
Roof				less Aluminum						
Roof Cap			•	ss Steel						
Interior Walls				, Engineered Wood						
Interior Trim			•	m Wall Transitions						
Ceiling		Insulation, Vinyl	Ceiling Transitions, V	White Vinyl Liner with	Aluminum Coves					
Flooring		· · ·	•	eered Wood						
Interior Lights			(2) 1	I" LED						







	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30			
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V								
Cargo Control	(4) 5000 lb. Recessed D-Rings								
Connector Plug	Round 7-pin Blade								
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights								
HVAC	Bracing and Wire for HVAC								





	ERICAN						
	8.5 x 32	8.5 x 34					
Model #	KP10232PRFBRT-140	KP10234PRFBRT-140					
CAPACITIES							
GVWR (lbs)	14000						
GAWR (lbs/axle)	7000						
CHASSIS							
Frame	8" x 2" S	Steel Tube					
Tongue	12" Extension, 8" x	2" Steel Triple Tube					
Crossmembers	Formed Steel	, 16" On-Center					
Coupler	2-5/16" /	Adjustable					
Safety Chains	DOT Co	ompliant					
Tongue Jack	7K Drop Le	eg, Set-Back					
Wall Studs	Steel Tube,	16" On-Center					
Roof Bows	Steel Tube,	16" On-Center					
Front Profile	F	ilat					
Beavertail	4	18"					
Ramp(s)	16" Extension with Bullnose Cap, (2) Re	ecessed Cam Locks, 4000 lb. with Assist					
Side Door	48" Aluminum Pull-Out Step, 48" Wide	e Flush Lock, Cast Aluminum Holdback					
Vents	(1) Manual Root	f, Sidewall Airflow					
Fenders	Extruded	Aluminum					
Axle	(2) 7000 lb. Torsion Brake	, Spread Axle Configuration					
Hubs	Easy	/ Lube					
Breakaway	Battery, Switch	ch, and Lanyard					
Tires	ST235/80	R16E 10-PR					
Wheels	16", 8-Hol	e Aluminum					
Exterior Finish	.040" A	luminum					
Undercoating	Auto	motive					
Exterior Fastening		d (Screwless)					
Exterior Trim		ion, Polished Cast Aluminum Roof Corners, Stainless Steel					
		nless Steel Rear Hoop					
Stone Guard		АТР					
Rear Spoiler		el Flare with Taper					
Roof	•	nless Aluminum					
Roof Cap		ess Steel					
Interior Walls		y, Engineered Wood					
Interior Trim		ım Wall Transitions					
Ceiling	· · · · · · · · · · · · · · · · · · ·	White Vinyl Liner with Aluminum Coves					
Flooring	•	eered Wood					
Interior Lights	· , ,	1" LED					
Switches	,,,,,	/, (1) Top Fuel Load Light, 12V					
Cargo Control	(4) 5000 lb. Re	ecessed D-Rings					







	8.5 x 32	8.5 x 34			
Connector Plug	Round 7-pin Blade				
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights				
HVAC	Bracing and \	Wire for HVAC			





	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34			
Madal #	KP10224PRFBRT-	KP10226PRFBRT-	KP10228PRFBRT-	KP10230PRFBRT-	KP10232PRFBRT-	KP10234PRFBRT-			
Model #	160	160	160	160	160	160			
CAPACITIES									
GVWR (lbs)			16	000					
GAWR (lbs/axle)			80	000					
CHASSIS									
Frame	8" x 2" Steel Tube								
Tongue			12" Extension, 8" x	2" Steel Triple Tube					
Crossmembers			•	16" On-Center					
Coupler			2-5/16" <i>A</i>	Adjustable					
Safety Chains			DOT Co	mpliant					
Tongue Jack			12K Drop Lo	eg, Set-Back					
Wall Studs			Steel Tube, 1	6" On-Center					
Roof Bows		Steel Tube, 16" On-Center							
Front Profile		Flat							
Beavertail	48"								
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist								
Side Door		48" Aluminum Pu	ıll-Out Step, 48" Wide	Flush Lock, Cast Alı	uminum Holdback				
Vents	(1) Manual Roof, Sidewall Airflow								
Fenders			Extruded	Aluminum					
Axle		(2) 80	000 lb. Torsion Brake,	· ·	ıration				
Hubs				Bath					
Breakaway			•	h, and Lanyard					
Tires				7.5J 18-PR					
Wheels			•	le Aluminum					
Exterior Finish				luminum					
Undercoating				notive					
Exterior Fastening	_			l (Screwless)					
Exterior Trim	5.5" Bottom Ext		uck Body Top Extrusi Radius Corners, Stair			s, Stainless Steel			
Stone Guard			•	ATP	μ				
Rear Spoiler				l Flare with Taper					
Roof				less Aluminum					
Roof Cap			•	ss Steel					
Interior Walls				, Engineered Wood					
Interior Trim			•	m Wall Transitions					
Ceiling		Insulation, Vinyl	Ceiling Transitions, V	White Vinyl Liner with	Aluminum Coves				
Flooring		. ,		eered Wood					
Interior Lights				1" LED					







	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34			
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V								
Cargo Control	(4) 5000 lb. Recessed D-Rings								
Connector Plug	Round 7-pin Blade								
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights								
HVAC	Bracing and Wire for HVAC								





	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34	
Model #	KP10226PRFBRT-210	KP10228PRFBRT-210	KP10230PRFBRT- 210	KP10232PRFBRT-210	KP10234PRFBRT-210	
CAPACITIES						
GVWR (lbs)			21000			
GAWR (lbs/axle)			7000			
CHASSIS						
Frame	8" x 2" S	teel Tube		8" x 2" S	teel Tube	
Tongue	12" Extension, 8" x	2" Steel Triple Tube		12" Extension, 8" x	2" Steel Triple Tube	
Crossmembers	Formed Steel,	16" On-Center		Formed Steel,	16" On-Center	
Coupler	2-5/16" <i>A</i>	djustable		2-5/16" <i>A</i>	Adjustable	
Safety Chains	DOT Co	mpliant		DOT Co	mpliant	
Tongue Jack	12K Drop Le	eg, Set-Back		12K Drop Lo	eg, Set-Back	
Wall Studs	Steel Tube, 1	6" On-Center		Steel Tube, 1	6" On-Center	
Roof Bows	Steel Tube, 1	6" On-Center		Steel Tube, 1	6" On-Center	
Front Profile	Fl	at		Flat		
Beavertail	4	8"		48"		
Ramp(s)		nose Cap, (2) Recessed 0 lb. with Assist		16" Extension with Bullnose Cap, (2) Recesse Cam Locks, 4000 lb. with Assist		
Side Door		tep, 48" Wide Flush Lock, um Holdback		48" Aluminum Pull-Out Step, 48" Wide Flush Loc Cast Aluminum Holdback		
Vents		(1) Ma	nual Roof, Sidewall	Airflow		
Fenders	Extruded	Aluminum		Extruded	Aluminum	
Axle	' '	Brake, Spread Axle uration		· · ·	n Brake, Spread Axle uration	
Hubs	Easy	Lube		Easy	Lube	
Breakaway	Battery, Switc	h, and Lanyard		Battery, Switc	h, and Lanyard	
Tires	ST235/80F	R16E 10-PR		ST235/80F	R16E 10-PR	
Wheels	16", 8-Hole	e Aluminum		16", 8-Hole	e Aluminum	
Exterior Finish	.040" A	uminum		.040" A	luminum	
Undercoating	Autor	notive		Autor	notive	
Exterior Fastening	VHB Bonded	(Screwless)		VHB Bonded	l (Screwless)	
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop			5.5" Bottom Extrusion, Heavy Duty Truck Bot Extrusion, Polished Cast Aluminum Roof Co Stainless Steel Radius Corners, Stainless S Rear Hoop		
Stone Guard	24" ATP			24" ATP		
Rear Spoiler	6" Stainless Stee	l Flare with Taper		6" Stainless Stee	el Flare with Taper	
Roof		less Aluminum		Flat Top Seamless Aluminum		
Roof Cap		ss Steel		•	ss Steel	







	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34	
Interior Walls	Aluminum Overlay, En	gineered Wood		Aluminum Overlay, Engineered Wood		
Interior Trim	Extruded Aluminum V	/all Transitions		Extruded Aluminu	m Wall Transitions	
Ceiling	Insul	ation, Vinyl Ceiling Tran	sitions, White Viny	Liner with Aluminum Cove	es	
Flooring	3/4" Engineered Wood			3/4" Engine	ered Wood	
Interior Lights	(2) 11" L	ED		(2) 11" LED		
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V			(1) Top Fuel Dome Light, 12V, (1) Top Fu Light, 12V		
Cargo Control	(4) 5000 lb. Reces	sed D-Rings		(4) 5000 lb. Recessed D-Rings		
Connector Plug	Round 7-pin	Blade		Round 7-pin Blade		
Exterior Lights	(2) Rear LED Loading, (4) Additional			(2) Rear LED Loading, (4) Additiona Stop/Turn/Tail, Full LED, DOT Complia Integrated Backup/Taillights		
HVAC	Bracing and Wire	for HVAC		Bracing and Wire for HVAC		



NOVAECORP.COM



	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26			
Model #	KP10220PRFBRT-070	KP10222PRFBRT-070	KP10224PRFBRT-070	KP10226PRFBRT-070			
CAPACITIES							
GVWR (lbs)	7000						
GAWR (Ibs/axle)	3500						
CHASSIS							
	6" y 9" Céanl Tuha						
Frame Tongue	6" x 2" Steel Tube						
Crossmembers	12" Extension, 6" x 2" Steel Triple Tube Formed Steel, 16" On-Center						
Coupler	2-5/16" Adjustable						
Safety Chains	DOT Compliant						
Tongue Jack	7K Drop Leg, Set-Back						
Wall Studs	Steel Tube, 16" On-Center						
Roof Bows	Steel Tube, 16" On-Center						
Front Profile	Flat						
Beavertail	32" 48"						
Ramp(s)	16" Extension with Bullnose Cap (Both Ramps), (2) Recessed Cam Locks, 4000 lb. with Assist						
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback						
Vents	(1) Manual Roof, Sidewall Airflow						
Fenders	Extruded Aluminum						
Axle	(2) 3500 lb. Torsion Brake, Spread Axle Configuration						
Hubs	Easy Lube						
Breakaway	Battery, Switch, and Lanyard						
Tires	ST205/75R15C 6-PR						
Wheels	15", 5-Hole Aluminum						
Exterior Finish	.030" Aluminum						
Undercoating	Automotive						
Exterior Fastening	VHB Bonded (Screwless)						
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel						
Stone Guard	Radius Corners, Stainless Steel Rear Hoop 24" ATP						
Rear Spoiler	6" Stainless Steel Flare with Taper						
Roof	Flat Top Seamless Aluminum						
Roof Cap	Stainless Steel						
Interior Walls	Aluminum Overlay, Engineered Wood						
Interior Trim	Extruded Aluminum Wall Transitions						
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves						
Flooring	3/4" Engineered Wood						
Interior Lights	(2) 11" LED						
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V						







	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26		
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
HVAC	Bracing and Wire for HVAC					

