



## **SHADOW GT FLAT TOP FLAT FRONT 24K**

	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 34				
Model #	KP10224PRFBSRT-BP-240	KP10226PRFBSRT-BP-240	KP10228PRFBSRT-BP-240	KP10234PRFBSRT-BP-240				
CAPACITIES								
GVWR (lbs)	24000							
GAWR (lbs/axle)	8000							
CHASSIS								
Frame	8" x 2" Steel Tube							
Tongue		6" Extension, 8" x :	2" Steel Triple Tube					
Crossmembers		Formed Steel,	16" On-Center					
Coupler		2-5/16" <i>A</i>	djustable					
Safety Chains		DOT Co	mpliant					
Tongue Jack		6K Hy	draulic					
Wall Studs		Steel 3" x 1" Tub	e, 16" On-Center					
Roof Bows		Steel Tube, 1	2" On-Center					
Front Profile	Flat							
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist							
Side Door	60" Aluminum Pull-Out Step, 60" Wide Double Flush Lock, Cast Aluminum Holdback							
Access Doors	36" x 33"Generator							
Vents	(1) Manual Roof, Sidewall Airflow							
Fenders	Extruded Aluminum							
Axle	(3) 8000 lb. Torsion Brake, Spread Axle Configuration							
Hubs		Oil	Bath					
Breakaway		Battery, Switc	h, and Lanyard					
Tires		215/75R17.5J 18-PR						
Wheels	17.5", 8-Hole Aluminum							
<b>Exterior Finish</b>	.080" Composite							
Undercoating		Autor	notive					
<b>Exterior Fastening</b>		VHB Bonded	l (Screwless)					
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Ste							
Stone Guard	Radius Corners, Stainless Steel Rear Hoop							
Rear Spoiler	24" ATP							
Roof	6" Stainless Steel Flare with Taper Flat Top Seamless Aluminum							
Roof Cap		•	ss Steel					
Exterior Accessories			Wheels					
Interior Walls								
Interior Trim	Aluminum Overlay, Engineered Wood 36" Carpet Wall Liner, Extruded Aluminum Wall Transitions							
Ceiling	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves							
Flooring	3/4" Engineered Wood, Black Rubber Tread Overlay							
Interior Lights	(10) 11" LED							
meno Lights	(10) 11 LED							



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





## **SHADOW GT FLAT TOP FLAT FRONT 24K**

	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 34		
Switches	(3) Pair Top Fuel 3-Way, 12V					
Fixtures	24" Full-Height Wardrobe, L-Shaped Base Cabinet, L-Shaped Overhead Cabinet, Storage Loft					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Interior Accessories	8' Removable Wall-Mount Ladder					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) 22" Rear Ramp LED Loading, (6) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
<b>Hydraulic Components</b>	14' 4-Post Auto Lift 16' 4-Post Auto Lift					
12v Electrical	12 Volt DC 24 Battery, Stereo with 4 Speakers, Subwoofer, USB Port and Receptacle					
110v Electrical	(1) Exterior GFI Receptacle, (4) Interior Receptacles, 50 Amp Motor Base Plug, 50 Amp Power Converter, 50 Amp					
I TOV Electrical	Power Cord, 50 Amp Service Panel, Air Compressor Prep, Generator Prep with Transfer Switch					
HVAC	Bracing and Wire for HVAC					







## **SHADOW GT FLAT TOP FLAT FRONT 21K**

	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34	
Madel #	KP10224PRFBSRT-	KP10226PRFBSRT-	KP10228PRFBSRT-	KP10230PRFBSRT-	KP10232PRFBSRT-	KP10234PRFBSRT-	
Model #	BP-210	BP-210	BP-210	BP-210	BP-210	BP-210	
CAPACITIES							
GVWR (lbs)			21	000			
GAWR (lbs/axle)			70	000			
CHASSIS							
Frame		8" x 2" Steel Tube					
Tongue				2" Steel Triple Tube			
Crossmembers			·	16" On-Center			
Coupler				Adjustable			
Safety Chains				mpliant			
Tongue Jack				draulic			
Wall Studs			•				
Roof Bows		Steel 3" x 1" Tube, 16" On-Center  Steel Tube, 12" On-Center					
Front Profile		Flat					
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist						
Side Door	60" Aluminum Pull-Out Step, 60" Wide Double Flush Lock, Cast Aluminum Holdback						
Access Doors	36" x 33"Generator						
Vents		(1) Manual Roof, Sidewall Airflow					
Fenders		Extruded Aluminum					
Axle		(3) 7000 lb. Torsion Brake, Spread Axle Configuration					
Hubs			Easy	Lube			
Breakaway			Battery, Switc	h, and Lanyard			
Tires		ST235/80R16E 10-PR					
Wheels		16", 8-Hole Aluminum					
<b>Exterior Finish</b>		.080" Composite					
Undercoating			Autor	motive			
<b>Exterior Fastening</b>		VHB Bonded (Screwless)					
Exterior Trim	5.5" Bottom Extrusion, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Radius Corners, Stainless Steel Rear Hoop					s, Stainless Steel	
LACETION TIME							
Stone Guard			24"	ATP			
Rear Spoiler		6" Stainless Steel Flare with Taper					
Roof		Flat Top Seamless Aluminum					
Roof Cap				ss Steel			
<b>Exterior Accessories</b>				Wheels			
Interior Walls		Aluminum Overlay, Engineered Wood					
Interior Trim		36" Carpet Wall Liner, Extruded Aluminum Wall Transitions					
Ceiling		Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
Flooring		3/4" Engineered Wood, Black Rubber Tread Overlay					
Interior Lights		(10) 11" LED					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

2025 Pricing





## **SHADOW GT FLAT TOP FLAT FRONT 21K**

	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Switches	(3) Pair Top Fuel 3-Way, 12V					
Fixtures	24" Full-Height Wardrobe, L-Shaped Base Cabinet, L-Shaped Overhead Cabinet, Storage Loft					
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Interior Accessories	8' Removable Wall-Mount Ladder					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) 22" Rear Ramp LED Loading, (6) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
<b>Hydraulic Components</b>	14' 4-Post Auto Lift 16' 4-Post Auto Lift					
12v Electrical	12 Volt DC 24 Battery, Stereo with 4 Speakers, Subwoofer, USB Port and Receptacle					
110v Electrical	(1) Exterior GFI Receptacle, (4) Interior Receptacles, 50 Amp Motor Base Plug, 50 Amp Power Converter, 50 Amp Power Cord, 50 Amp Service Panel, Air Compressor Prep, Generator Prep with Transfer Switch					
HVAC	Bracing and Wire for HVAC					

